

IAPMO RESEARCH AND TESTING, INC.

5001 E. Philadelphia Street, Ontario, CA 91761 • Phone (909) 472-4100 • Fax (909) 472-4244 • www.iapmort.org



CERTIFICATE OF LISTING

NSF/ANSI/CAN 61

IAPMO Research and Testing, Inc. is a product certification body in which its product certification system includes inspection and testing of samples taken from the supplier's stock or from the market or a combination of both to verify compliance to the requirements of applicable codes and standards. This activity is coupled with periodic surveillance of the supplier's factory and/or warehouses as well as the assessment of the supplier's Quality Assurance System. This listing is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO Research and Testing, Inc. of the product acceptance by Authorities Having Jurisdiction.

Issued To:

FANSKI GROUP INC.

MECHANICAL & ELECTRICAL INDUSTRIAL ZONE, YUHUAN COUNTY, YUHUAN 317600, ZHEJIANG, CHINA

Product:

Drinking Water System Components - Health Effects

Products are certified to the following standard(s)

NSF/ANSI/CAN 61-2023

File Number: N-6632

Revised Date: February 26, 2025

Effective Date: December 2024

Void After: December 2029*


Chairman, Product Certification Committee




Chief Technical Service Officer

*This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

This listing period is based upon the last date of the month indicated on the Effective Date and Void After Date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of the Product Certification Committee, or any evidence of non-compliance with applicable codes and standards or of inferior workmanship, may be deemed sufficient cause for revocation of this listing. Production of or reference to this form for advertising purposes may be made only by specific written permission of IAPMO Research and Testing, Inc. Any alteration of this certificate could be grounds for revocation of the listing. This document shall be reproduced in its entirety.

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

NSF/ANSI/CAN 61	Issued To: FANSKI GROUP INC.	Effective Date: December 2024
	File Number: N-6632	Revised Date: February 26, 2025
	Product: Drinking Water System Components - Health Effects	Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Identification:

Each product shall be permanently and legibly marked with the manufacturer's name or trademark. The product may also be marked with the standard designation "NSF/ANSI/CAN 61".

Characteristics:

Materials or products that come into contact with drinking water and/or drinking water treatment chemicals. Products and materials may include process media, protective materials, joining and sealing materials, pipes and related products, mechanical devices used with treatment/transmission/distribution systems, and mechanical plumbing devices. To be installed in accordance with the manufacturer's instruction. Lead free requirements are addressed under a separate certificate of listing.

Products listed on this certificate have been tested by an IAPMO R&T recognized laboratory. This recognition has been granted based upon the laboratory's compliance to the applicable requirements of ISO/IEC 17025.

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Models

Note: The following models are in compliance with NSF/ANSI 61, section 9.

Note 2: For models indicated with a subscript "Q" the lead statistic Q value are in compliance with the "Optional Lower Lead Requirements" per Section 9.5.1.1 of NSF/ANSI/CAN 61-2022

Series 1: SS Braided connectors

Model Number	Description
QDG301-X	S.S. Braided, 3/8" C x 1/2" FIP
QDG302-X	S.S. Braided, 1/2" FIP x 1/2" FIP
QDG303-X	S.S. Braided, 1/2" FIP x M 1/2"
"X"	indicates lengths up to 1,800mm

Legend Format	Description
QDG(1)(2)(3)(4)(5)(6)-(7)	
(1)	Braided Material
1	Stainless Steel braided
2	Pet braided
3	Stainless Steel braided with PVC Coating
5	Nylon braided
7	PVC Reinforced
9	Polymer braided (for PVC inner tube only)
(2)	Inner Core tubing Type
P	Single PVC (lengths 009" to 245")
V	Double PVC (lengths 009" to 245")
H	HDPE (for lengths 009" to 300")
T	Santoprene (lengths 009- 254")

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

(2)	Inner Core tubing Type
X	PEX (lengths 009" to 72")
(3)	Inlet Fitting Type Options
M	Male
F	Female
(4)	Inlet Fittings Size options
a	M12x1
b	M8x1.25
c	3/8"
A	3/8C*3/8MIP Elbow
B	1/2"
C	3/4"
D	1/4"C
E	3/8"C
F	1/2"C
G	7/8" Ballcock
H	3/4"NH
I	M10x1
J	3/4" NH Elbow
K	3/8"OD Copper tubing
L	1/2" Flare
M	3/8"Flare
N	7/16"C
O	5/8"OD
P	7/8"OD
S	1/2" Push fit
T	3/4 Push fit
U	5/16"
V	M8x1
W	M14x1

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

(4)	Inlet Fittings Size options
X	M15x1
Y	Non-threaded end
Q	3/8C*1/2FIP Adaptor
R	3/8C*3/4NH Elbow
Z	3/8C*1/2C Adaptor
(5)	Outlet Fitting Type Options
M	Male
F	Female
(6)	Outlet Fitting Size Options
a	M12x1
b	M8x1.25
c	3/8"
A	3/8C*3/8MIP Elbow
b	M8x1.25
B	1/2"
C	3/4"
D	1/4"C
E	3/8"C
F	1/2"C
G	7/8" Ballcock
H	3/4"NH
I	M10x1
J	3/4" NH Elbow
K	3/8"OD Copper tubing
L	1/2" Flare
M	3/8"Flare
N	7/16"C
O	5/8"OD
P	7/8"OD

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

(6)	Outlet Fitting Size Options
S	1/2" Push fit
T	3/4 Push fit
U	5/16"
V	M8x1
W	M14x1
X	M15x1
Y	Non-threaded end
Q	3/8C*1/2FIP Adaptor
R	3/8C*3/4NH Elbow
Z	3/8C*1/2C Adaptor

(7) Any number 009 to 072 indicating overall length (inches) of connectors

Series 2: Brass Wire Braided Connectors

Model Number	Description
QDG2VFAFB-xx	Polished Brass Faucet Connector 3/8"C x 1/2"F
QDG2VFAFG-xx	Polished Brass Braided Connector 3/8"C x 7/8"

Series 3: Plastic (PEX) Connectors

Model Number	Description
QDG4NNB-xx	Plastic (PEX) Faucet Supply Tube 3/8" (9~36")
QDG4NNG-xx	Plastic (PEX) Toilet Supply Tube 3/8" (9~36")

Series 6: Copper Connectors

Model Number	Description
QDG8NNBB-xx	3/8" Copper Faucet Supply (9~36")- Ven Bronze
QDG8NNBB-xx	3/8" Copper Faucet Supply (9~36")- Chrome
QDG8NNBN-xx	3/8" Copper Faucet Supply(9~36")- Brushed Nickel
QDG8NNBP-xx	3/8" Copper Faucet Supply(9~36")- Polished Brass

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Model Number	Description
QDG8NNGB-xx	3/8" Copper Toilet Supply (9~36")- Ven Bronze
QDG8NNGC-xx	3/8" Copper Toilet Supply (9~36")- Chrome
QDG8NNGN-xx	3/8" Copper Toilet Supply(9~36")- Brushed Nickel
QDG8NNGP-xx	3/8" Copper Toilet Supply (9~36")- Polished Brass

Series 1: Stop Valves

Legend Format	Description
Q ^F — x — x — x — x — x	
1st x	can be replaced with the following code indicating the valve style:
Q	Quarter turn
M	Multi turn
2nd x	can be replaced with the following code indicating the body style:
A	Angle type
S	Straight type
3rd x	can be replaced with the following code indicating the inlet style:
0	3/8" FIP
1	3/8" OD Com (1/4" Nom.Com)
2	1/2" FIP
3	1/2" OD Com (3/8" Nom.Com)
4	5/8" OD (1/2" Nom.Com)
5	1/2" SWEAT
6	1/2" PEX
7	1/2" CPVC
8	1/4" OD Com
9	7/16" OD (7/16"&1/2" Slip-Joint)
4th x	can be replaced with the following code indicating the outlet style:
0	3/8" FIP

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

4th x	can be replaced with the following code indicating the outlet style:
1	3/8" OD Com (1/4" Nom.Com)
2	1/2" FIP
3	1/2" OD Com (3/8" Nom.Com)
4	5/8" OD (1/2" Nom.Com)
5	1/2" SWEAT
6	1/2" PEX
7	1/2" CPVC
8	1/4" OD Com
9	7/16" OD (7/16"&1/2" Slip-Joint)
5th x	can be replaced with the following code indicating the finish:
P	Chrome
R	Rough (no coating)

Series 2: Stop valve with hose

Model Number	Description
QDG1VFCNU	1/2" Push fit valve x 3/4" FIP braided hose(Max. Length 24")
QDG1VFCNV	3/4" Push fit valve x 3/4" FIP braided hose(Max. Length 24")

Model Number	Description
F0204-12704-12	PVC Pipe 1/2 OD X 1/4 ID
F0204-15904-01	PVC Pipe 5/8 OD X3/8 ID
F0204-22204-01	PVC Pipe 7/8 OD X5/8 ID
F0204-19004-01,	PVC Pipe 3/4 OD X1/2 ID
F0204-25404-01	PVC Pipe 1 ODX3/4 ID
F0204-34904-01	PVC Pipe 1 3/8 OD X 1 ID
F0204-44504-01	PVC Pipe 1 3/4 OD X 1 1/4 ID
F0204-50804-01	PVC Pipe 2 OD X 1 1/2 ID
F0204-63504-01	PVC Pipe 2 1/2 OD X 2 ID
F0203-12704-01	PVC Pipe 1/2 OD X3/8 ID BLACK

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Stainless Steel Corrugated Water-heater Connectors

Legend Format	Description
DG60 (1)(2)(3)(4)-(5)	
(1)	Inlet Fitting Type Options
M	Male
F	Female
(2)	Inlet Fittings Size options
C	3/4" FIP
K	3/4" SWEAT
L	3/4" PEX
M	3/4" MIP
N	3/4" PUSH FIT
O	1" FIP
P	1-1/4" FIP
Q	1-1/2" FIP
R	2" FIP
(3)	Outlet Fitting Type Options
M	Male
F	Female
(4)	Outlet Fitting Size Options
C	3/4" FIP
K	3/4" SWEAT
L	3/4" PEX
M	3/4" MIP
N	3/4" PUSH FIT
O	1" FIP
P	1-1/4" FIP

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Issued To: FANSKI GROUP INC.

Effective Date: December 2024

NSF/ANSI/CAN 61

File Number: N-6632

Revised Date: February 26, 2025

Product: Drinking Water System Components - Health Effects

Void After: December 2029

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

(4)	Outlet Fitting Size Options
Q	1-1/2" FIP
R	2" FIP
(5)	Indicates the length. Max. 24"

Copper Corrugated Water-heater Connectors

Legend Format	Description
DG80 (1)(2)(3)(4)-(5)	
(1)	Inlet Fitting Type Options
M	Male
F	Female
(2)	Inlet Fittings Size options
C	3/4" FIP
K	3/4" SWEAT
L	3/4" PEX
M	3/4" MIP
(3)	Outlet Fitting Type Options
M	Male
F	Female
(4)	Outlet Fitting Size Options
C	3/4" FIP
K	3/4" SWEAT
L	3/4" PEX
M	3/4" MIP
(5)	Indicates the length. Max. 24"