



BIANCO VULCAN 5.0 HP TANKER PUMP

The pump is a compact self priming engine driven pump supplied ready to operate with hose fittings and suction strainer.

The pump is characterised by:

- Single Cylinder, 4 Stroke, Forced Air Cooled Briggs & Stratton OHV Engine
- Heads to 30 metres
- Flows to 500 l/m
- Suction to 6m/120s
- 2" BSP Male Discharge Port
- 2" BSP Male Suction Port
- Rubber Mounting Feet
- Low Oil Level Engine Protection

Features:

- Next generation engine and pump design
- 800 hour high performance engine
- Dura-bore™ cast iron cylinder liners for longer life
- Lo-Tone™ muffler for reduced noise
- Low emissions to recognised global standards
- Full national engine support across 400+ Briggs & Stratton service centres
- Spark arrester with deflector
- Low oil sensor
- Full serviceability without removing pump from frame
- Heavy duty fuel cap
- Multi-Point discharge port
- Custom built frame

Applications:

- Dust Suppression
- Water Transfer
- Tank Filling
- Water Cartage

Liquid:	Engine Data:
Liquid Type: Clean Water Clean water temperature range: 2 - 35° C	Type: Single Cylinder, Aircooled, 4 Stroke OHV, Briggs & Stratton I/C Series
Materials:	Model: 1062320070H1
Pump Body: Aluminium	HP gross: 5.0
Impeller: Aluminium	Displacement: 163 cc
Mechanical Seal: Carbon/Ceramic/Nitrile	Air Cleaner: Dual Element, Paper and Foam
O rings: Nitrile	Ignition: CDI
Installation:	Starting: Recoil
Maximum ambient temperature: 40°C	Fuel Capacity: 3.1 Litre
Self Priming Time at 5m: <120 seconds	Oil Capacity: 0.6 Litre
Weight:	
24kg	

