



MEDIA DETAILS

Filter-Ag Plus is a unique natural ore called clinoptilolite that offers many outstanding advantages over common granular filter sands and multimedia used for suspended solids reduction.

The Filter-Ag Plus structure typically creates less pressure loss through the filter, allowing deeper sediment penetration into the bed for higher sediment loading and longer filter runs. Longer filter run times reduce backwash frequency, thereby conserving water.

Filter-Ag Plus has a nominal micron rating of 5 µm.

COMPONENTS

- Pre-programmed Clack® CT valve
- 1252 media vessel
- Media: Filter-Ag or Filter-Ag Plus

CERTIFICATIONS

- NSF/ANSI 44
- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- Watermark Pending



INFLUENT WATER

Site-specific water quality is assessed for suitability

WATER TEMP

+4 to 30° C

SPECIFICATIONS

INPUT POWER	230V, 50 Hz
POWER CONSUMPTION	30W
INLET PRESSURE	2 - 6 bar
OPERATING FLOW RATE	≈ 14.1 L/min
PRESSURE DROP	0.5 - 1 bar in service mode
REGENERATION	15 - 30 minutes @ 28.8 l/min
REGENERATION WATER	400 - 800 L
MEDIA	56.6L FLAGPL
INLET / OUTLET	1"
CHAMBER DIMENSIONS	Ø 310mm x 1533mm high incl valve



Certified to
NSF/ANSI 44



PRODUCT DETAILS

The WS1 TC automatic control valve is designed as the primary control to manage filter backwashing when paired with FPA Carbon Filters, FNA Neutralising Filters and FP Sediment Filters up to 16" diameter.

The valve provides 2 options for backwash frequency

- an option where the user can choose the number of days (1-99) between backwashes; or
- a seven-day option where the user can choose which day(s) of the week the backwash should occur.

FEATURES

- Informative 4 digit LCD Display with Status Indicators
- Solid state microprocessor with easy access front panel settings
- Backwash ability up to 16" diameter tanks
- Front panel display for time of day, days until next regeneration
- Double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Coin Cell Lithium battery back-up with a 8 hour carry over
- 12-volt output AC Adapter provides safe and easy installation
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Reliable and proven DC drive

SPECIFICATIONS

SUPPLY VOLTAGE	230V, 50 Hz
OUTPUT VOLTAGE	12VDC
OUTPUT CURRENT	500mA
MAX INLET PRESSURE	2 - 6 bar
MAX FLOW RATE	≤ 102 L/min
PRESSURE DROP	0.5 bar in service mode 1.7 bar in backwash mode
INLET / OUTLET	1" NPT
MOUNTING BASE	2 1/2"
HEIGHT FROM TOP OF TANK	187mm
WEIGHT	2kg

COMPONENTS

- Clack® CT valve
- AC Adaptor powerpack

