



PRODUCT DETAILS

A stylish space-saving cabinet softener designed for smaller spaces, homes and apartments. Supplied with media and inbuilt brine tank. Fully automated, silent operation.

FEATURES

- Made in Belgium with 100% US-made equipment
- Reliable US-made Clack® CE valve
- Large salt capacity – up to 117 kg
- Built-in mixing valve
- Smart overflow location saves installation space and protects against mechanical damage

COMPONENTS

- Pre-programmed Clack® CE valve
- Cabinet enclosure
- 1235 media chamber
- Brine well with safety float valve

CERTIFICATIONS

- NSF/ANSI 44
- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372



INFLUENT WATER

HARDNESS	750 mg/L CaCO ₃
IRON	0.2 mg/L
MANGANESE	0.05 mg/L
CHEMICAL O ₂ DEMAND	5 mg/L O ₂
PREFILTRATION	≤100 µm
WATER TEMP	+4 to 30° C
CHLORINE	≤5 ppm
PH	0 - 14
TDS	≤5000

SPECIFICATIONS

INPUT POWER	230V, 50 Hz
POWER CONSUMPTION	30W
INLET PRESSURE	2 - 6 bar
OPERATING FLOW RATE	36 - 46 L/min
PRESSURE DROP	0.5bar in service mode
VOLUME CAPACITY	7500L @ 250mg/L CaCO ₃ incoming water hardness
SALT CONSUMPTION	3.7 - 6.0 kg per regeneration
REGENERATION	80 - 110 minutes
REGENERATION WATER	370 L
MEDIA	37L DOWEX®
INLET / OUTLET	1"
DRY WEIGHT	30kg
DIMENSIONS MM	350W x 520D x 1130H